


PRECISION HEAVY DUTY TAPERED THREADS

Gives a Strong Reliable Seal. Material is strong enough to minimise potential cross threading.



MADE FROM HIGH QUALITY DURABLE MATERIALS

Manufactured from UV Stabilised High Quality Glass Fibre Reinforced Nylon giving a weather, termite, fungi and bacterial resistance

AS/NZS 4020


POTABLE WATER APPROVED

Material Approved for use with Potable (drinkable) Water



MAXIMUM WORKING PRESSURE

Female Tank Fittings:

Sizes 15 - 50mm (1/2" to 2") 16 Bar (232 psi) @ 20°C

Sizes 80 - 100mm (3" - 4") 10 Bar (145 psi) @ 20°C

Male Tank Fittings:

Sizes 15 - 50mm (1/2" to 2") 16 Bar (232 psi) @ 20°C



QUALITY WASHERS FOR A POSITIVE SEAL

High quality, durable Thermoplastic Elastomer Rubber & Low Density Polyethylene washers for a positive reliable seal.



COMPREHENSIVE RANGE

Female Tank Fittings available in sizes 15mm to 100mm (1/2" to 4"). Male Tank Fittings available in Black or White & sizes 15mm to 50mm (1/2" to 2"). Tank Plugs available in 50mm (2").



EASY TO INSTALL

Installing a Hansen Tank Fitting is a simple, straight forward procedure. Below is an outline of the steps.

See our website for full info including hole sizes and tips.

1. Drill a hole in the tank. Remove the nut and first 'firmer' washer from fitting and insert the fitting in hole.



2. On the other side of the tank, reinsert the washer and wind the nut back on



3. Tighten the nut so that the face of both washers make full contact with the tank wall for a water tight seal. Your done!



4. When adding additional fittings, use a thread sealing paste or thread tape.



HANSEN
True Fit Tank Fittings

Reliable Commercial Quality Tank Fittings

www.hansenproducts.com